

MNR 150

HYDRAULIC COMPARISON TEST PUMP

- RUGGED AND SOLID DESIGN, STAINLESS STEEL
- EASY PRIMING AND PRESSURE GENERATION
- EASY TO OPERATE
- LARGE 26 CC VOLUME DISPLACEMENT



also water in case the devices should not be contaminated with oil due to the

application for which it is used.



TECHNICAL SPECIFICATIONS

Models	MNR 150 - 700, 0 - 700 bar oil (70 MPa / 10.000 psi)
	MNR 150 - 1000, 0 - 1000 bar water (100 MPa / 15.000 psi)
	MNR 150 - 1400, 0 - 1400 bar oil (140 MPa / 20.000 psi)
Supply	Set of adapters; 1 x 1/8" BSP, 1 x 1/4" BSP, 1 x 3/8" BSP, 2 x 1/2" BSP
	and 1/2 liter Nuto H32-oil
Material:	
connections	2 x 3/8" BSP left male
bottom plate	Stainless steel with four mounting holes for stable setting
filling fluids	Suitable for oil and water (other fluids on request)
wetted parts	Pump stainless steel, nitryl and viton seals and brass adapters

RELATED PRODUCTS

- MNR 130 Dirt / moisture trap
- MNR 140 Oil-gas separator





your distributor:



Minerva meettechniek B.V.

Chrysantstraat 1
3812 WX Amersfoort, the Netherlands
tel. +31 33 46 22 000
info@minervaipm.com